



Energy Information Made Obvius

Flex I/O Module

Analog/Digital to Modbus Converter



FLEX I/O A8332-8F2D

Our Flex I/O is a cost-effective way to collect data from meters or sensors and bring that information into a Modbus network or energy monitoring system. As a stand-alone or bundled package, the Obvius Flex I/O can be incorporated with data acquisition and wireless metering devices to provide a cost-effective energy monitoring solution.

WHY USE THE OBVIUS FLEX I/O

- Designed specifically for metering applications
- Easily add meters and sensor to a Modbus network
- 8x user selectable inputs
- 2x output relays
- 2x pulse replicator
- Non-volatile memory
- Industrial temperature range -30 to 70C
- LEDs for visual verification / status
- Din or wall mount for easy installation
- Field upgradable firmware

COMPATIBILITY

The Flex I/O is compatible with virtually any Modbus master, allowing customers the flexibility to use it in existing Modbus networks. Use with the Obvius AcquiSuite and take advantage of plug-and-play communication or us with the Obvius ModHopper for wireless communication.

PARTNERS

Obvius' outstanding integration and software partners supplement our products and services to ensure you receive the very best energy monitoring solution.

APPLICATIONS

- Converting analog, resistive and pulse inputs to Modbus
- Utility submetering (electric, gas, water, etc.)
- Cost Allocation
- Measurement and Verification
- Benchmark building energy usage
- Relay outputs for demand control
- Environmental monitoring
- Track energy use and peak demand for Demand Response
- DC current monitoring for Renewable Energy

ABOUT OBVIUS

Obvius manufactures data acquisition and wireless connectivity products specifically for energy management. We deliver cost-effective, reliable hardware designed to speed up installation. Our products are based on an open architecture allowing our customers to collect and log energy information from virtually any meter or sensor. The ability to support multiple communication options provides remote access to all your energy information. Founded in 2003, Obvius is located in Hillsboro, Oregon. We serve a global clientele and continue to drive innovation by simplifying data collection.

SOLUTIONS

- Data Acquisition
- Wireless Communication
- Meters & Sensors
- Custom Packaged Solutions
- Integration & Software Partners

HEADQUARTERS

Hillsboro, Oregon

CONTACT US

sales@obvius.com

Flex IO – A8332-8F2D

Obvius helps customers collect and distribute energy information. Users can begin with one best-of-breed solution that solves a specific pain point, or incorporate several products and services that help reduce energy costs.

Specifications

Processor	ARM7, field upgradeable firmware
LEDs	8x input status LEDs (red), 2x Modbus TX/RX (yellow), 1 power/alive status (green)
Memory	Pulse count and runtime values are stored in non-volatile memory

Power

Power Supply	24VDC, 200mA but not to exceed 8A, Required (not included)
--------------	--

Communication

Protocols	Modbus/RTU
-----------	------------

Inputs

Voltage Mode	0-10VDC (min/max/average/instantaneous data) Accuracy: +/- 0.25% of full scale at 20C
Current Mode	4/20mA (min/max/average/instantaneous data) Accuracy +/- 0.25% of full scale at 20C
Resistance Mode	100 ohms to 100k (see installation for accuracy specification)
Pulse Mode	<ul style="list-style-type: none">Intended for use with dry contact outputs (consumption/rate/runtime/status)Standard and KYZ modes for form A and C relay outputsInput terminals supplies 5V at 5mA sense voltage to detect contact closuresMaximum rate: 10Hz, minimum pulse width 50msAdjustable contact closure threshold: 100Ω to 5kΩ, broken wire sense above 10kΩ optional
Serial Port	RS-485 two wire, 19200 or 9600 baud, 8N1
I/O	8 Flex IO inputs with user selectable modes: voltage, current, resistance, pulse and status
Isolation	Pulse outputs and RS485 port are isolated to 1500VDC; Power input, RS232 and analog/pulse inputs are non-isolated

Outputs

Relays	2x, dry contact (opto-fet) 30 VDC, 150 mA max
--------	---

Physical

Weight	3.7oz (105g)
Size	4.13" x 3.39" x 1.18" (105mm x 86mm x 30mm)

Environment

North America	-30 to 70C, 0-95% RH, non-condensing
Altitude	2000M max
Pollution	Degree 2

Codes and Standards

Emissions	FCC CFR 47 Part 15, Class A, EN 61000, EN 61326
Safety	UL61010 Recognized, EN61010

Additional Notes

NEMA enclosures available upon request.

For use with any Modbus RTU device / server



Obvius
3300 NW 211th Terrace
Hillsboro, OR 97124

503 601 2099
866 204 8134 (USA only)
sales@obvius.com